

Marlow DATASHEET[®]

VIPER2 SLING

A factory sewn CE certified eye-to-eye sling made using a high strength cord incorporating the proven Viper Vectran cover. Viper2 slings have short stitching for efficient technique.



APPLICATIONS: Prussik

MATERIAL

COVER: Vectran / Polyester
CORE: 12 strand Vectran

CONSTRUCTION

TEST STANDARDS: CE EN 566
PROPERTIES: High strength termination conforms to CE EN 566
COLOURS: Purple / natural

TERMINATIONS

Sewn eyes
Serial numbered, factory CNC sewn terminations for regulatory compliance

PERFORMANCE

DIAMETER	LENGTH	WEIGHT	AVERAGE BREAK LOAD	MINIMUM BREAK LOAD
mm	cm	g	kN	kN
8	50	57.2	23.6	22
8	60	64.6	23.6	22
8	70	72	23.6	22
8	80	75.5	23.6	22
8	90	80.9	23.6	22
8	1M	86.2	23.6	22

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

www.marlowropes.com
UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.
Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.
Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.
Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.
MA-DA-085 | ISSUE NO.2



Certification Number 315
ISO 9001